
TUBIBOND UV T

Characterization	Adhesive with elastic film properties used for fast and strong paper bonding applications.
Chemical Structure	Phthalate free, polyvinylacetate homopolymer
Supplied Form	White viscous liquid
Ionic character	Anionic
pH Value	4.0 – 5.0
Viscosity at 20 °C	1500 – 2500 cp
Storage	With a proper storage conditions at 5 - 40°C in closed original containers, the product holds for at least six months.

Properties

TUBIBOND UV T is free of phthalate group which is restricted according to several international standards.

TUBIBOND UV T has visibility properties under UV light.

TUBIBOND UV T forms clear and elastic films. TUBIBOND UV T is suitable to use in all kind of serial packaging machines by having well adjusted viscosity and drying properties. TUBIBOND UV T forms clear and elastic films. Due to possible changes in viscosity, pay attention to the ambient temperature (room temperature).

Application technique

Diluting instructions

TUBIBOND UV T can be diluted with water (not above 5 %) while stirring.

Application fields

TUBIBOND UV T can be used in the manufacturing process of cardboard, corrugated cardboard, paper-to-paper boxes.

The changes that may occur in the viscosity due to temperature need to pay attention. It is recommended to control the ambient temperature while working with the product.

We reserve the right to modify the product and technical leaflet.

Our department for applied technique is always at your service for further information and advice.

Our technical advice and recommendations given verbally, in writing or by trials are believed to be correct. They are neither binding with regard to possible rights of third parties nor do they exempt you from your task of examining the suitability of our products for the intended use. We cannot accept any responsibility for application and processing methods which are beyond our control.

Edition: July, 2024

CHT GERMANY GMBH, P.O. Box 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany

Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, homepage: www.cht.com

CHT TURKEY KİMYA SAN. VE TİC.A.Ş., Akçaburgaz Mah. 3118. Sok. No:2 Esenyurt/İstanbul, Tel: +90 212 886 79 13, Fax:+90 212 886 93 47,

Email: info.turkey@cht.com