

TUT E 728

Characterization	Adhesive for label.
Chemical Structure	Vinyl acrylic copolymer
Supplied Form	White, viscose fluid
pH Value (%10)	4.0 – 5.0
Ionic character	Anionic
Viscosity	15000 – 20000 cps (RVT, spindle:5, 20 rpm)
Storability	TUT E 728 can be stored for at least 12 months in closed original containers between 5 and 30°C.

Properties

TUT E 728 can be used directly machine systems for all kinds of labeling and packaging processes. The product forms clear and elastic film.

Application technique

Diluting instructions

TUT E 728 can be diluted with water (not above 20%) while stirring.

Application fields

TUT E 728 can be applied by hand or by machine when sticking labels onto synthetic packaging such as polyethylene and polyester.

We reserve the right to modify the product and technical leaflet.

Our department for applied technique is always at your service for further information and advice.

Our technical advice and recommendations given verbally, in writing or by trials are believed to be correct. They are neither binding with regard to possible rights of third parties nor do they exempt you from your task of examining the suitability of our products for the intended use. We cannot accept any responsibility for application and processing methods which are beyond our control.

Edition: August, 2024

CHT GERMANY GMBH, P.O. Box 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany

Telephone: 07071/154-0, **Fax:** 07071/154-290, **Email:** info@cht.com, **homepage:** www.cht.com

CHT TURKEY KİMYA SAN. VE TİC.A.Ş., Akçaburgaz Mah. 3118. Sok. No:2 Esenyurt/İstanbul, Tel: +90 212 886 79 13, **Fax:**+90 212 886 93 47,

Email: info.turkey@cht.com