

---

## TUBIJET® FAST P12

<b>Character</b>	Post-treatment for digital pigment printing on textiles to improve fastness and softness.
<b>Chemical Composition</b>	Emulsion of modified siloxane
<b>Appearance</b>	Liquid, white emulsion
<b>Ionic Character</b>	Nonionic
<b>pH Value</b>	5,5 – 7,0
<b>Solubility</b>	TUBIJET® FAST P12 is miscible with water.
<b>Stabilities</b>	Can be used together with nonionic, anionic or cationic products.
<b>Storage</b>	<p>Stir before removal. Store in a cool and dry place in tightly closed, original containers. Opened containers must be closed again tightly. We recommend not exceeding a storage time of 12 months.</p> <p>The product is sensitive to frost; after the impact of temperatures below the freezing point irreversible changes occur. Storage temperatures below 5 °C and above 40 °C can highly reduce the shelf life of the product.</p>

---

The above given values are product describing data. Please consult the 'delivery specification' for binding product specifications. Further data about product properties, toxicological, ecological data as well as data relevant to safety can be found in the safety data sheet.

## Properties

TUBIJET® FAST P12 is a universally applicable product that is used for the post-treatment of textiles in digital pigment printing. The product improves the fastness and soft hand by a high surface smoothness. Thus, the abrasion is reduced and the longevity of printed textiles is improved. It can be used with all fiber materials and offers the following advantages:

- Improves crock and wash fastness
- Soft hand
- Formaldehyde-free\*

® = registered trademark

## Technical Guidelines

### Application

Method: Padding

Diluting instructions: The product can be diluted with cold water to any ratio. Be sure to mix well.

Cleaning instructions: Before use, we recommend rinsing all vessels and especially the pumps with water in order to prevent any contamination with anionic substances which could cause precipitations.

### Process

- Primer application before printing by foulard

For further recipe please see [https://www.cht.com/cht/web.nsf/id/pa\\_inkjet-druck.html](https://www.cht.com/cht/web.nsf/id/pa_inkjet-druck.html).

- Digital printing

- Fixation 160 °C 3 min

- Post-treatment (if required)

Can be applied directly after drying of the digital print and before the final fixation.

Products	Recipe
TUBIJET® FAST P12	30 g/l
TUBIJET® FAST P11	30 g/l

\* To us formaldehyde-free means that all recipe components neither contain nor release formaldehyde during production or processing.

**We reserve the right to modify the product and technical leaflet.**

**Our department for applied technique is always at your service for further information and advice.**

Our technical advice and recommendations given verbally, in writing or by trials are believed to be correct. They are neither binding with regard to possible rights of third parties nor do they exempt you from your task of examining the suitability of our products for the intended use. We cannot accept any responsibility for application and processing methods which are beyond our control.

**Edition:** April, 2024.

**CHT GERMANY GMBH, P.O. Box 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany**  
**Telephone: 07071/154-0, Fax: 07071/154-290, Email: [info@cht.com](mailto:info@cht.com), homepage: [www.cht.com](http://www.cht.com)**  
**CHT TURKEY KİMYA SAN. VE TİC.A.Ş., Akçaburgaz Mah. 3118. Sok. No:2 Esenyurt/İstanbul,**  
**Tel: +90 212 886 79 13, Fax:+90 212 886 93 47,**  
**Email: [info.turkey@cht.com](mailto:info.turkey@cht.com)**