

TUT TX 1200

Characterization	Adhesive with elastic film properties used for fast and strong paper bonding applications
Chemical Structure	Latex
Supplied Form	Beige liquid
pH Value	9.8 – 11.2
Viscosity at 20 °C	< 1000 cps (LVT - spindle:1,2,3 - 50 rpm)
Storage	On proper storage in closed original containers, the product is stable for at least 12 months. The product must be protected from humidity.

Properties

TUT TX 1200 can be used without dilution in machine work. The product forms clear and elastic films and has a quick dry property. In boxes using TUT TX 1200, adhesion is achieved when two surfaces see each other even after a long waiting period.

Application technique

Application fields

TUT TX 1200 can be used in lamination processes in the manufacturing process of cardboard, corrugated cardboard, book binding papers and paper-to-paper box production.

We reserve the right to modify the product and technical leaflet.

Our department for applied technique is always at your service for further information and advice.

Our technical advice and recommendations given verbally, in writing or by trials are believed to be correct. They are neither binding with regard to possible rights of third parties nor do they exempt you from your task of examining the suitability of our products for the intended use. We cannot accept any responsibility for application and processing methods which are beyond our control.

Edition: August, 2024

CHT GERMANY GMBH, P.O. Box 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany

Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, homepage: www.cht.com

CHT TURKEY KİMYA SAN. VE TİC.A.Ş., Akçaburgaz Mah. 3118. Sok. No:2 Esenyurt/İstanbul, Tel: +90 212 886 79 13, Fax:+90 212 886 93 47,

Email: info.turkey@cht.com