
TUT TX 35 P

Characterization	Adhesive for paper, paperboards, and paper bags
Chemical Structure	Phthalate free, polyvinyl acetate homopolymer
Supplied Form	White viscous liquid
Ionic character	Anionic
pH Value	4.5 – 5.5
Viscosity at 20 °C	1500 – 2500 cp
Storage	With proper storage condition at 5 - 25°C in closed original containers, the product holds for at least 12 months.

Properties

TUT TX 35 P is free of phthalate group which is restricted according to several international standards.

TUT TX 35 P is used in all kinds of paper and paper lamination processes, paper bag patch-handle and side seaming processes. TUT TX 35 P forms clear and elastic films. TUT TX 35 P is suitable to use in all kinds of serial packaging machines by having well adjusted viscosity and drying properties. TUT TX 35 P can be used directly or diluted with water.

Application technique

Diluting instructions

TUT TX 35 P can be diluted with water by mixing under the ratio of 5 %.

Application fields

TUT TX 35 P can be used in paper spinning machines, paper bag machines, all kinds of paper and paper lamination processes, box binding machines. It is also suitable for filter machine applications. TUT TX 35 P is especially suitable for tube production.

The changes that may occur in the viscosity due to temperature need to pay attention. It is recommended to control the ambient temperature while working with the product.

We reserve the right to modify the product and technical leaflet.

Our department for applied technique is always at your service for further information and advice.

Our technical advice and recommendations given verbally, in writing or by trials are believed to be correct. They are neither binding with regard to possible rights of third parties nor do they exempt you from your task of examining the suitability of our products for the intended use. We cannot accept any responsibility for application and processing methods which are beyond our control.

Edition: July 2024

CHT GERMANY GMBH, P.O. Box 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany

Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, homepage: www.cht.com

CHT TURKEY KİMYA SAN. VE TİC.A.Ş., Akçaburgaz Mah. 3118. Sok. No:2 Esenyurt/İstanbul, Tel: :+90 212 886 79 13, Fax:+90 212 886 93 47,

Email: info.turkey@cht.com